# Community Development Department

## **BUILDING INSPECTIONS INFO SHEET**

# **HOMEOWNER PROJECTS CODE REQUIREMENTS**

### **ELECTRICAL**

- Outlet box locations:
  - 6-foot, 12-foot rule, on walls 2-feet or greater in length in habitable rooms
  - ARC fault requirements all branch circuits, except bathroom, kitchen, laundry and exterior. NEC 210.12(B)
  - GFCI requirements
  - Caulk penetrations in exterior wall outlet boxes (lighting and receptacles)
- Lights fan rated boxes
- Secure wire within 12-inches of any box and minimum of every 4-feet
- Smoke Detector & Carbon Monoxide Detector requirement.
- Maintain clearance in front of electric service panel 30" wide, 36" out from panel face.

#### **PLUMBING**

- Toilet clearance:
  - o 15-inches from center to finished wall or cabinet
  - o 24-inches minimum clearance from front edge of stool
- Vent requirements for waste lines.

## **HVAC**

- Provide a supply and return duct for each habitable room.
- Exhaust fans required for the bathroom and terminated at the home exterior.
- No electrical boxes allowed in the return air duct. Electrical wires can only run perpendicular through the return air duct cavity.
- No plumbing allowed in the return air duct.
- Caulk all penetrations in the return air duct, spray foam not allowed.

### CONSTRUCTION

- Doors minimum 32-inch wide doors required for:
  - ½ of the bedrooms
  - o 1 full bath
  - All common area doors (utility room, storage room, office, etc.)
- Soffits draft stopping
- Egress windows basement and 2<sup>nd</sup> floor bedrooms:
  - 46-inches maximum allowed height from finished floor to the lowest point of clear window opening.
  - o Minimum clear opening of 24-inches by 20-inches.

NOT ALL INCLUSIVE – for more details check the WI State Admin Codes SPS 320-325.

#### FOR MORE INFORMATION